



**PO Box 1700  
Snohomish, WA USA 98291  
(425) 293-5763**

## **WAM B-102**

### **Boiler Treatment**

#### **Application**

WAM B-102 is a boiler feedwater corrosion inhibitor in an easy to feed liquid formula. It removes traces of oxygen that escape the deaerator.

#### **Dosage**

The feed rate is dependent upon the amount of dissolved oxygen in the boiler and the operating pressure, as well as load. Consult your Waterside Asset Management representative for assistance.

#### **Feeding**

WAM B-102 is best applied to the deaerator storage section in conjunction with the neutralizing amine. Do not feed it upstream from the takeoff point for desuperheat or attemperation water. An alternate feed point is directly to the boiler drum. It may be mixed with other boiler chemicals.

#### **Packaging**

Available in polyethylene drums and totes.

#### **Technical Data**

Form	Liquid
Color	Colorless
Specific Gravity (g/mL)	1.268
Density lb/gal (kg/L)	10.6 (1.27)
pH (neat)	7.4 to 8.4
pH (1% solution)	7.4 to 8.4

Acceptable for use in food processing plants as determined in 21CFR Section 173.310, Food and Drug. This product is constructed with materials previously authorized by the USDA for use in federally inspected meat and poultry plants.

#### **Safety Data**

Do not open this container or use its contents without first reading the material safety data sheet. If one is not available, call (425) 293-5763 for a replacement.

*March 7, 2006/ WBWT1AH-SF*