



**PO Box 1700  
Snohomish, WA USA 98291  
(425) 293-5763**

## **WAM B-202**

### **Boiler Treatment**

#### **Application**

WAM B-202 is a blended internal boiler water treatment product that will sequester hardness and condition sludge to maintain clean heat exchanges surfaces. This product contains a synthetic dispersant to condition suspended materials until they are removed from the boiler via blowdown.

#### **Dosage**

Dosage will depend on feedwater hardness and boiler pressure. Consult your Waterside Asset Management representative for assistance.

#### **Feeding**

WAM B-202 should be fed direct to the boiler in such a manner that it will be thoroughly mixed with incoming feedwater. Feed should be continuous and proportional to flow.

#### **Packaging**

Available in polyethylene drums and totes.

#### **Technical Data**

Form	Liquid
Color	Dark Brown
Specific Gravity (g/mL)	1.069
Density lb/gal (kg/L)	8.92 ( 1.07)
pH (neat)	8.9 to 9.9
pH (1% solution)	not determined

Acceptable for use in food processing plants as determined in 21CFR Section 173.310, Food and Drug. This product is constructed with materials previously authorized by the USDA for use in federally inspected meat and poultry plants.

#### **Safety Data**

Do not open this container or use its contents without first reading the material safety data sheet. If one is not available, call (425) 293-5763 for a replacement.

*March 7, 2006/ WBWT2EC-SF*