



**PO Box 1700
Snohomish, WA USA 98291
(425) 293-5763**

WAM B-624

Boiler Treatment

Application

WAM B-624 is an all-in-one drum treatment program for the prevention of scale and corrosion in boilers. This product maintains boiler sludge in a fluid, dispersed state allowing it to be removed from the boiler by normal blowdown. It will function best when applied to softened water. This formula includes corrosion inhibition for condensate systems.

Dosage

Exact dosages are dependent on feedwater hardness, oxygen and silica. Consult your Waterside Asset Management representative for assistance.

Feeding

WAM B-624 can be diluted with water or fed directly from the drum. It is advisable to feed the solution directly to the boiler to prevent deposits in the feedwater line.

Packaging

Available in polyethylene drums and totes.

Technical Data

Form	Liquid
Color	Dark Amber
Specific Gravity (g/mL)	1.103
Density lb/gal (kg/L)	9.20 (1.103)
pH (neat)	>13
pH (1% solution)	11.4 to 12.4

Acceptable for use in food processing plants as determined in 21CFR Section 173.310, Food and Drug. This product is constructed with materials previously authorized by the USDA for use in federally inspected meat and poultry plants.

Safety Data

Do not open this container or use its contents without first reading the material safety data sheet. If one is not available, call (425) 293-5763 for a replacement.

