



**PO Box 1700  
Snohomish, WA USA 98291  
(425) 293-5763**

## **WAM S-240**

### **Condensate Treatment**

#### **Application**

WAM S-240 is a blend of neutralizing amines employed for the complete protection of heat exchange equipment from corrosion in condensate return systems.

#### **Dosage**

Dosages will vary according to the severity of the feedwater carbonate activity. Consult your Waterside Asset Management representative for assistance.

#### **Feeding**

WAM S-240 should be pumped directly from the container to the boiler or the steam header. If it is fed from a tank with other treatment materials, utilize the best quality dilution water available.

#### **Packaging**

Available in polyethylene drums, totes, and in bulk.

#### **Technical Data**

Form	Liquid
Color	Colorless
Specific Gravity (g/mL)	1.003
Density lb/gal (kg/L)	8.37 (1.00)
pH (neat)	11.0 to 12.0
pH (1% solution)	9.6 to 10.6

Acceptable for use in food processing plants as determined in 21CFR Section 173.310, Food and Drug. This product is constructed with materials previously authorized by the USDA for use in federally inspected meat and poultry plants.

#### **Safety Data**

Do not open this container or use its contents without first reading the material safety data sheet. If one is not available, call (425) 293-5763 for a replacement.

*March 7, 2006/WCRT1BC-SF*